

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SPIT OIL SPRAY
Product code : SPIT - 318790-310080

1.2. Relevant identified uses of the substance or mixture and uses advised against

N/A

1.3. Details of the supplier of the safety data sheet

Registered company name : ITW Construction Products
Address : Fleming Way, Crawley, West Sussex RH10 9DP
Telephone : +44(0)1293 523372

1.4. Emergency telephone number : 112.

Association/Organisation : European emergency number.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).
Repeated exposure may cause skin dryness or cracking (EUH066).
Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Extremely flammable (F+, R 12).
Repeated exposure may cause skin dryness or cracking (R 66).
Aquatic environmental hazard, chronic toxicity: toxic (N, R 51/53).

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS09



GHS02

Signal Word :

DANGER

Hazard statements :

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statements - Prevention :

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
------	---

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Precautionary statements - Storage :

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Precautionary statements - Disposal :

P501 Dispose of contents/container at a disposal facility in accordance with local regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	67/548/EEC	Note	%
CAS: 8042-47-5 EC: 232-455-8 REACH: 01-2119487078-27 WHITE MINERAL OIL (PETROLEUM)	GHS08 Dgr Asp. Tox. 1, H304			25 \leq x % < 50
CAS: 64742-48-9 EC: 918-481-9 REACH: 01-2119457273-39 HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS	GHS08 Dgr Asp. Tox. 1, H304 EUH:066	Xn Xn;R65 R66		25 \leq x % < 50
CAS: 40027-38-1 EC: 254-754-2 REACH: 01-2119974119-29 OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYL PROPANE-1,3-DIAMINE	GHS07, GHS09, GHS08 Wng Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10	Xn,N Xn;R48/22 Xi;R36/38 N;R50/53		1 \leq x % < 2.5

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of splashes or contact with eyes :**

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

WHITE MINERAL OIL (PETROLEUM) (CAS: 8042-47-5)

Final use:

Workers.

Exposure method:

Dermal contact.

Potential health effects:

Long term systemic effects.

DNEL :

220 mg/kg body weight/day

Exposure method:

Inhalation.

Potential health effects:

Long term systemic effects.

DNEL :

160 mg of substance/m3

Final use:

Consumers.

Exposure method:

Ingestion.

Potential health effects:

Long term systemic effects.

DNEL :

40 mg/kg body weight/day

Exposure method:

Dermal contact.

Potential health effects:

Long term systemic effects.

DNEL :

92 mg/kg body weight/day

Exposure method:

Inhalation.

Potential health effects:

Long term systemic effects.

DNEL : 35 mg of substance/m3

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Fluid liquid.
	Spray.

Important health, safety and environmental information

pH :	Not relevant.
Boiling point/boiling range :	185 °C.
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).
Density :	< 1
Water solubility :	Insoluble.
Viscosity:	v < 7 mm2/s (40°C)
Self-ignition temperature :	250 °C.
Decomposition point/decomposition range :	250 °C.
Chemical combustion heat :	Not specified.
Inflammation time :	Not specified.
Deflagration density :	Not specified.
Inflammation distance :	Not specified.
Flame height :	Not specified.
Flame duration :	Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- humidity
- accumulation of electrostatic charges.
- flames and hot surfaces

10.5. Incompatible materials

Keep away from :

- water
- strong oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)

Oral route : LD50 > 5000 mg/kg
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 2000 mg/kg
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route : LC50 %@IDC_LA_INHAL_QUANTIFIERS 5000 %@IDC_LA_INHAL_UNITS

WHITE MINERAL OIL (PETROLEUM) (CAS: 8042-47-5)

Oral route : LD50 > 5000 mg/kg
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 5000 mg/kg
Species : Rabbit
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route : LC50 > 5000 mg/m³
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)

Respiratory or skin sensitisation :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)
Local lymph node stimulation test : Non-Sensitiser.

Germ cell mutagenicity :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)
No mutagenic effect.

Carcinogenicity :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)
Carcinogenicity Test : Negative.

No carcinogenic effect.

Reproductive toxicant :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)
No toxic effect for reproduction

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 40027-38-1)
Crustacean toxicity : EC50 = 0.048 mg/l
Factor M = 10
Species : Daphnia magna
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

EC10 %@IDC_ECOTOXSUB_CRUST_ECX_QUANTIFIERS %@IDED_ECOTOXSUB_CRUST_ECX_VALUE
mg/l
Species : Daphnia magna
Duration of exposure : 21 days
OECD Guideline 211 (Daphnia magna Reproduction Test)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)
Fish toxicity : LC50 > 1000 mg/l
Species : Oncorhynchus mykiss
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC50 > 1000 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity : ECr50 > 1000 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 40027-38-1)

Biodegradability : Rapidly degradable.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)
Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 40027-38-1)
Octanol/water partition coefficient : log K_{ow} = 33

Bioaccumulation : BCF = 71

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

-

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	2.1	See SP63	-	SP277	F-D,S-U	63 190 277 327 344 959	E0			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A145 A167 A802	E0	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Directive 75/734/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

- Container information:

No data available.

- Particular provisions :


No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :



Dangerous for the environment



Extremely flammable

Risk phrase :

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 12 Extremely flammable.

R 66 Repeated exposure may cause skin dryness or cracking.

Safety phrase :

S 16 Keep away from sources of ignition - No smoking.

S 2 Keep out of the reach of children.

S 29 Do not empty into drains.

S 46 If swallowed, seek medical advice immediately and show this container or label.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

S 51 Use only in well-ventilated areas.

Title for H, EUH and R indications mentioned in section 3 :

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
R 36/38	Irritating to eyes and skin.
R 48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
R 50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65	Harmful: may cause lung damage if swallowed.
R 66	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

DNEL : Derived No-Effect Level

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS09 : Environment