





hotun Dry Trap Tundish

15mm x 22mm hotun Dry Trap Tundish

Advanced Water Company, Unit D5 The Enterprise Centre, Off Enterprise Way, Vale Park, Evesham, Worcestershire, WR11 1GS
Tel: 01386 760066 | FAX: 01386 760077 | Email sales@advancedwater.co.uk

15mm x 22mm hotun Dry Trap Tundish

Description

The revolutionary hotun dry trap tundish allows the Temperature & Pressure relief valve to connect directly to the internal waste or soil pipe eliminating the need for external discharge. The non-return valve within the hotun Hiflo dry trap Tundish stops any foul odours from entering up through the Tundish and back into the building. The hotun dry trap tundish allows for easy identification of the historical PRV discharge by touch without the need to dismantle the connection. The hotun has been approved for use by several big-name boiler and water heater manufacturers and with it's 10 year guarantee it is the perfect solution to any hot water system.

Hotun Shield

Please note the hotun shield is not suitable for use on the hotun dry trap tundish.



Features

Dry Trap Tundish

Allows the PRV discharge to be compliantly connected to drain without odours

Eliminates the need for external discharge

Connects directly to internal waste or soil pipe

Approved for use by many major companies

Suitable for small unvented up to 15 Litres

Simple, easy to install solution

No odours

Available in black and white

Flow rate of 12L/min

10 Year Guarantee

Note: If purchasing for a boiler a hotun shield will need to be purchased

10 Year Guarantee

Product Specification

Inlet	1/2" Flat Faced Tap Connector
Outlet	22mm copper compression
Suitable For	Unvented cylinder up to 15 Litre in capacity
Colour	Available in Black & White

Part Codes

AWC Product Code	Description
231-597-0701	Hotun Black
231-597-0702	Hotun White

www.advancedwater.co.uk

