# 





# hotun hiflo Dry Trap Tundish

15mm x 32mm hotun hiflo Dry Trap Tundish

Advanced Water Company, Unit D5 The Enterprise Centre, Off Enterprise Way, Vale Park, Evesham, Worcestershire, WR11 1GS
Tel: 01386 760066 | FAX: 01386 760077 | Email sales@advancedwater.co.uk

# 15mm x 32mm hotun hiflo Dry Trap Tundish

# Description

The revolutionary hotun hiflo dry trap tundish allows the Temperature & Pressure relief valve to connect directly to the internal waste or soil pipe eliminating the need for external discharge. The non-return valve within the hotun Hiflo dry trap Tundish stops any foul odours from entering up through the Tundish and back into the building. The hotun dry trap tundish allows for easy identification of the historical PRV discharge by touch without the need to dismantle the connection. The hotun hiflo has been approved for use by several big-name boiler and water heater manufacturers and with it's 10 year guarantee it is the perfect solution to any hot water system.

## Hotun Shield

The hotun shield is required on any purchase of the hotun higflo when used in conjunction with a boiler or where an airgap is not required. The hotun shield allows discharging water to be seen clearly and allows for safe installation in accessible areas. The simple drop-over design is simple to use and once the top connection is made the shield is held securely in place. It should not suitable for any unvented product.



### **Features**

### Dry Trap Tundish

Allows the PRV discharge to be compliantly connected to drain without odours

Eliminates the need for external discharge

Connects directly to internal waste or soil pipe

Approved for use by many major companies

Suitable for Unvented Cylinders

Suitable for Boilers & Water Heaters over 15 Litres

Simple, easy to install solution

### No odours

Available in black and white

### **Durable material**

Independently verified flow rate of 18L/min

10 Year Guarantee

# **Product Specification**

Inlet	1/2" Flat Faced Tap Connector
Outlet	32mm universal compatible plain spigot
Suitable For	Boiler or unvented water heater (max flow rate from PRV 18L/min)
Colour	Available in Black & White

# **Part Codes**

<b>AWC Product Code</b>	Description
231-597-0001	Hotun Hiflo Black
231-597-0002	Hotun Hiflo White
231-551-0001	Hotun Shield

www.advancedwater.co.uk

